

1/4" 15-TURN, SQUARE, CERMET TRIMMER POTENTIOMETERS

Specifications:

- Tolerance: $\pm 10\%$
- Oper. temp. range: -55°C to $+155^{\circ}\text{C}$
- Rated voltage: 250VD
- Rotation: 15 turns ± 5
- Power rating: .25W @ 85°C
- Temperature coefficient: $\pm 70\text{ppm}/^{\circ}\text{C}$
- Screwdriver slot: $.02" \times .02"$

For quantities 500 and up, call for quote.

MOUSER STOCK NO.	Fig.	Table of Values (Ω)	Price Each				
			1	25	50	100	200
72-T63YB-Value	A	10, 20, 50, 100, 200, 500, 1K, 2K, 5K, 10K, 20K, 25K, 50K, 100K, 100K, 200K, 250K, 500K, 1M	2.49	2.27	2.13	1.99	1.68
72-T63XB-Value	B		2.49	2.27	2.13	1.99	1.68
72-T63ZB-Value	C		2.49	2.27	2.13	1.99	1.68

1/4" 13-TURN SMD, SQUARE, CERMET TRIMMER POTENTIOMETERS

Specifications:

- Tolerance: $\pm 10\%$
- Oper. temp. range: -55°C to $+155^{\circ}\text{C}$
- Rated voltage: 250VD
- Rotation: 13 turns ± 2
- Power rating: .25W @ 85°C
- Temperature coefficient: $\pm 50\text{ppm}/^{\circ}\text{C}$
- Screwdriver slot: $.02" \times .02"$

Surface Mount Device

For quantities 500 and up, call for quote.

MOUSER STOCK NO.	Fig.	Table of Values (Ω)	Price Each				
			1	25	50	100	200
72-TS63Y-Value	D	10, 20, 50, 100, 200, 500, 1K, 2K, 5K, 10K, 20K, 25K, 50K, 100K, 200K, 250K, 500K, 1M, 2M	2.89	2.35	1.88	1.72	1.51

3/4" 15-TURN, RECTANGULAR, HORIZONTAL ADJUST, CERMET TRIMMER POTENTIOMETERS

Specifications:

- Tolerance: $\pm 10\%$
- Oper. temp. range: -55°C to $+155^{\circ}\text{C}$
- Rated voltage: 250VDC
- Rotation: 15 turns ± 1
- Power rating: .75W @ 70°C
- Temperature coefficient: $\pm 70\text{ppm}/^{\circ}\text{C}$
- Screwdriver slot: $.024" \times .024"$

For quantities 500 and up, call for quote.

MOUSER STOCK NO.	Fig.	Table of Values (Ω)	Price Each				
			1	25	50	100	200
72-T18-Value	E	100, 200, 500, 1K, 2K, 5K, 10K, 20K, 25K, 50K, 100K, 200K, 500K, 1M, 2M	1.24	1.19	1.15	1.05	.884

3/8" 19-TURN, SQUARE, CERMET TRIMMER POTENTIOMETERS


Specifications:

- Tolerance: $\pm 10\%$
- Oper. temp. range: -55°C to $+155^{\circ}\text{C}$
- Operating temperature range: -55°C to $+155^{\circ}\text{C}$
- Rotation: 19 turns ± 2
- Power rating: .50W @ 85°C
- Temperature coefficient: $\pm 70\text{ppm}/^{\circ}\text{C}$
- Screwdriver slot: $.024" \times .024"$


For quantities 500 and up, call for quote.

MOUSER STOCK NO.	Fig.	Table of Values (Ω)	Price Each				
			1	25	50	100	200
72-T93XA-Value	F	10, 20, 50, 100, 200, 500, 1K, 2K, 5K, 10K, 20K, 25K, 50K, 100K, 200K, 250K, 500K, 1M, 2M	1.20	1.15	1.10	1.05	.901
72-T93XB-Value	G		1.20	1.15	1.10	1.05	.901
72-T93YA-Value	H		1.20	1.15	1.10	1.05	.901
72-T93YB-Value	I		1.20	1.15	1.10	1.05	.901
72-T93Z-Value	J		2.34	2.24	2.15	2.05	1.72

MOUSER STOCK NO.	Kit Contains 90 Pieces	Price Each
370-T93XA-KIT 370-T93XB-KIT 370-T93YA-KIT 370-T93YB-KIT 370-T93Z-KIT	10 each: 1K, 5K, 10K 5 each: 10, 50, 100, 500, 2K, 20K, 50K, 100K, 200K, 500K, 1M, 2M	99.95



MOUSER STOCK NO.	Kit Contains 90 Pieces	Price Each
370-T18-KIT	10 each: 1K, 5K, 10K 5 each: 100, 200, 500, 2K, 20K, 25K, 50K, 100K, 200K, 500K, 1M, 2M	99.95



DIMENSIONS (IN.)

A

B

Screwdriver slot: .02x.02

C

D

E

F

G

H

I

J