



> Products > Connector > Pin Header / Socket > Pin Header 2.54mm Board Spacer

- Connector
- Customized
- PCB Jack
- Pin Header / Socket
- IDC Flat Cable Connector
- USB Connector
- FFC / FPC Connector
- Memory Card Connector
- D-Sub / Hoods
- Centronics
- Mini. Din / Din
- DC Connector
- Audio / Video Connector
- PCB Connector
- Water Proof Connector

- Cable
- Telecom



**Pin Header 2.54mm Board Spacer**

**Material**

Insulator: PBT + GF or Nylon (UL94V-0)  
 Contact: Brass or Phosphor Bronze  
 RoHS Compliant

**Specification**

Contact Resistance: 30mΩ Max. AT 1 AMP  
 Insulator Resistance: 1,000MΩ Min. AT 500VDC  
 Current Rating: 1 AMP  
 Operating Temperature: -55°C to +105°C  
 Dielectric Withstanding Vol.: 500 Vdc Min.

**How to order**

Series No.	No. of Pins	Pin Type	Plating	Row Type
B22	40	1	1	1
	01~80	1: Straight M: SMT	1: Gold Flash 2: Tin	1: Single 2: Double
Code	Pin Material	Post	Cap	
x	B	2	B	
Refer to Code Form (Upon Customer's Design)	B: Brass P: Phos. bronze	black: w/o 2: w post	black: w/o B: with	

**Optional Dimensions**

